**SIDEX**

solutions provider for the steel industry



Dasa-Rägister

UNI EN ISO 9001:2015

IQ-0120-01


**EN 10051:** Nastri laminati a caldo in continuo e lamiere/fogli tagliati da nastri larghi di acciai non legati e legati  
 tolleranze sulle dimensioni e sulla forma  
*Hot rolled continuously casted strips and sheets/plates cut from strips in alloyed and unalloyed steels*  
*Tolerance on dimensions and shape*

Tolleranze sullo spessore - *Tolerances on thickness*NORMALI - *normal*

Spessore nominale <i>Nominal thickness</i>	Tolleranze per una larghezza nominale <i>Tolerance for nominal width</i>			
	≤ 1200	> 1200 ≤ 1500	> 1500 ≤ 1800	> 1800
≤ 2,00	± 0,17	± 0,19	± 0,21	-
> 2,00 ≤ 2,50	± 0,18	± 0,21	± 0,23	± 0,25
> 2,50 ≤ 3,00	± 0,20	± 0,22	± 0,24	± 0,26
> 3,00 ≤ 4,00	± 0,22	± 0,24	± 0,26	± 0,27
> 4,00 ≤ 5,00	± 0,24	± 0,26	± 0,28	± 0,29
> 5,00 ≤ 6,00	± 0,26	± 0,28	± 0,29	± 0,31
> 6,00 ≤ 8,00	± 0,29	± 0,30	± 0,31	± 0,35
> 8,00 ≤ 10,00	± 0,32	± 0,33	± 0,34	± 0,40
> 10,00 ≤ 12,50	± 0,35	± 0,36	± 0,37	± 0,43
> 12,50 ≤ 15,00	± 0,37	± 0,38	± 0,40	± 0,46
> 15,00 ≤ 25,00	± 0,40	± 0,42	± 0,45	± 0,50

RISTRETTE e SPECIALI - *restricted (3/4 standard) and special (2/3 standard)*

Spessore nominale <i>Nominal thickness</i>	Tolleranze per una larghezza nominale <i>Tolerance for nominal width</i>							
	≤ 1200		> 1200 ≤ 1500		> 1500 ≤ 1800		> 1800	
	R	S	R	S	R	S	R	S
≤ 2,00	± 0,13	± 0,11	± 0,14	± 0,13	± 0,16	± 0,14	-	-
> 2,00 ≤ 2,50	± 0,14	± 0,12	± 0,16	± 0,14	± 0,17	± 0,15	-	-
> 2,50 ≤ 3,00	± 0,15	± 0,13	± 0,17	± 0,15	± 0,18	± 0,16	-	-
> 3,00 ≤ 4,00	± 0,17	± 0,15	± 0,18	± 0,16	± 0,20	± 0,17	-	-
> 4,00 ≤ 5,00	± 0,18	± 0,16	± 0,20	± 0,17	± 0,21	± 0,19	-	-
> 5,00 ≤ 6,00	± 0,20	± 0,17	± 0,21	± 0,19	± 0,22	± 0,19	-	-

**SIDEX**

solutions provider for the steel industry



Dasa-Rägister

UNI EN ISO 9001:2015  
IQ-0120-01Tolleranze sulla lunghezza - *Tolerances on length*

<b>Lunghezza nominale mm</b> <i>Nominal length</i>	<b>Tolleranza mm</b> <i>Tolerance m</i>
< 2000	-0 / +10mm
≥ 2000 <8000	-0 / +0,005 x length
≥ 8000	-0 / +40mm

Tolleranze sulla larghezza - *Tolerances on width*

<b>larghezza nominale mm</b> <i>Nominal width</i>	<b>Bordi grezzi</b> <i>Raw edges</i>	<b>Bordi rifilati</b> <i>Trimmed edges</i>
	<b>Tolleranza mm</b> <i>Tolerance m</i>	<b>Tolleranza mm</b> <i>Tolerance m</i>
< 2000	-0 / +20 mm	-0 / +3 mm
≥ 2000 <8000	-0 / +20mm	-0 / +5 mm
≥ 8000	-0 / +25 mm	-0 / +6 mm